



Made in JAPAN

COUMARONE INDENE RESIN H-100


HIGHLY EFFECTIVE RESIN FOR ANTI-CORROSIVE COATING / PAINT
(REACH/RoHS Compliant) Consistent Quality



(Coumarone)



(Indene)



(Styrene)

Characteristics:

1. Low Molecular Weight <700, Helps in faster Dissolutions, Solubility & Strength.
2. Excellent Tack Retention.
3. Excellent Heat Resistance.
4. Available in Golden color Pallets / Beads.

Advantages:

1. Imparts Salt Water (Sea) / Chemical Resistant Properties.
2. It will keep Protecting all kinds of Steel Structure for long time.
3. Faster Drying Better Gloss Cost Effective Strong Bond to Steel Excellent Heat Resistance. For ship building Paint.
4. Resistance to Biological Attack.
5. Better Low Temperature Flexibility.

COUMARONE	INDENE	STYRENE
High cohesiveness Better Knitting, Chemical Resistance.	Better Adhesiveness, Increase Tack	Heat Resistance (Better Heat Ageing)
Water Proofing, Sealing & Corrosion Resistance.	Glutinosity (Helps to maintain Viscosity)	Increase Gas Impermeability

Other Grades of C I Resin: CI Resin G-90, V-120 & Liquid L-5, L-20.

Made in JAPAN

ARAKYD 9201 N



ONE PACK HIGH MOLECULAR WEIGHT EPOXY RESIN

Characteristics:

1. No need of using Hardner and hence no issue of Shelf Life and No Residual Wastage.
2. High Performance Anti Corrosive Primer/Coatings for Metal Substrates.
3. Excellent Anti Corrosive and Chemical Resistance Properties.

Made in JAPAN



TOSOH CORPORATION

PETCOAL-120 HIGH PERFORMANCE HYDROCARBON RESIN

AROMATIC AND ALIPHATIC CO-POLYMER OF C5/C9
PETROTACK

AROMATIC HYDROCARBON (PETROLEUM RESIN) C9
PETCOAL


PETROTACK and **PETCOAL** are having Outstanding properties which Exhibits Excellent Compatibility with Solvents, Others Resins, Fats and Oils. They have good Thermal Stability and Weathering Property, Outstanding Resistance to Acids, Alkalis, and water. Fine Thermal Stability.

PETCOAL 120 is Light Colored Aromatic Hydrocarbon Resin for Metallic and Light Shades Paints with improved Gloss and Clarity of Paints / Coating

Other Grades of Petrotack & Petcoal:

Petrotack: Petrotack 60, Petrotack 70, Petrotack 90, Petrotack 100V. **Petcoal:** Petcoal LX, Petcoal 140.

Made in UK



INNOVOX-95 CALCIUM OXIDE POWDER (EFFECTIVE DESICCANT)

Innovox-95 is 95% Microfine Powdered Calcium Oxide with 5% Mineral oil Coating (Uniform Dispersion / Prevent fly Loss)

Applications:

1. High Corrosion Resistance & Superior Alkali Resistance Performance in Powder Coating and Paint.
2. Innovox-95 acts as Defoamer in Epoxy Based Powder Coating during Curing Process.

For Detailed Literature, Sample, Formulation & Requirement Contact

Mr. Chintan Makhecha 7878166277



BOMBAY CHEMICAL & RUBBER PRODUCTS

609, Raheja Centre, Free Press Journal Marg, Nariman Point, Mumbai – 400 021
Tel. No.022-22040474 / 22820440 | Email : info@bomchem.com | Website : www.bomchem.com

We The Rubber People... Together as One ... We Can... We Do...
Mumbai . Delhi . Chennai . Pune . Ahmedabad . Kolkata